

# Orange Circular

## Control Cable

Australian standard control cable

### Construction:

Class 2 stranding, white with black numbered PVC insulation, flame retardant, UV resistant orange PVC sheath, meter marked.

### Minimum Bending Radius:

12 x cable diameter

### Nominal Voltage:

600/1000V

### Relevant Standard:

AS/NZS1125, AS/NZS3808, AS/NZS5000.1, flame retardant to IEC60332-1, RoHS compliant, UV stabilised.

### Temperature Range:

-20°C to +90°C



RALOS AS ORANGE CIRCULAR CONTROL

Type	Cores x CSA	Conductor Diameter	Insulation Thickness	Insulation Diameter	Laid Up Diameter	Outer Sheath Thickness	Overall Diameter	Max. 20°C DC. Conductor Resistance	Approx Weight
Part No.	mm <sup>2</sup>	mm	mm	mm	mm	mm	mm	Ω/km	kg/km
OC7G1.5	6C1.5+E1.5	1.5	0.8	3.1	9.3	1.8	13.2	13.6	256
OC11G1.5	10C1.5+E1.5	1.5	0.8	3.1	12.4	1.8	16.3	13.6	377
OC16G1.5	15C1.5+E1.5	1.5	0.8	3.1	14.6	1.8	18.7	13.6	511
OC21G1.5	20C1.5+E1.5	1.5	0.8	3.1	16.5	1.8	20.6	13.6	632
OC7G2.5	6C2.5+E2.5	2.0	0.8	3.6	10.8	1.8	14.9	7.41	356
OC11G2.5	10C2.5+E2.5	2.0	0.8	3.6	14.4	1.8	18.5	7.41	535
OC16G2.5	15C2.5+E2.5	2.0	0.8	3.6	16.9	1.8	21.0	7.41	511